

INEOS Oligomers

Sales Specification

Indopol[®] Polybutene Grade: H-1500

| SPECIFICATIONS PROPERTIES | METHOD/ASTM NUMBER (if applicable) | | VALUE |
|--|------------------------------------|-------------|---------------------|
| Viscosity (cSt) Min Max Temp (°C) | Kinematic | D 445 | 2900 3200 100 |
| Color (Hazen),max | Pt-Co Scale | mod. D 1209 | 50 |
| Flash Point (°C), min | Pensky-Martens Closed cup | D 93 | 170 |
| Water (ppm), max | Coulimetric Karl-Fischer | E 1064 | 40 |
| Appearance (Clear & Bright) | Visual | n/a | C&B |



Technical information contained herein is furnished without charge or obligation, and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, INEOS makes no representation about, and is not responsible or liable for the accuracy or reliability of data, nor for toxicological effects or Industrial Hygiene requirements associated with particular uses of any product described herein. Nothing contained in this document shall be considered a recommendation for any use that may infringe patent rights, or an endorsement of any particular material, equipment, service, or other item not supplied by INEOS. The "Properties" and "Applications" listed in this document are not specifications. They are provided as information only and in no way modify, amend, enlarge, or create any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED.

The name INEOS is a trademark of INEOS Capital Limited.
September, 2008